

TILTING PRECISION FOR MAXIMUM EFFICIENCY

 Twin-lock Front and Rear

 Universal OEM Capabilities

 ISO13031/AS13031 Compliance

 5 Year Extended Warranty Available

GTT

Suitable for machines
from 1-6t

Miller's GTT – quick hydraulic tilt coupler – delivers exceptional versatility whilst enabling fast and easy attachment changes. Achieving up to 180° of tilt rotation, operators can achieve a wide range of motion, simplifying a complex job, whilst remaining in just one position. Increasing productivity, our lightweight tilt coupler can often eliminate the need for additional specialised equipment, reducing costs.



FEATURES

1. Lower Offset Design

A low-profile design that optimises pin-to-point geometry for efficient digging and stability, even when tilting at extreme angles.

2. Front Latch

An independent, bi-directional front latch system that remains firmly locked under tilt motions, allowing operators to safely operate and detach attachments at a wide range of angles.

3. 180° Rotary Actuator

A fully integrated tilt system that provides guaranteed rotation of 180°, delivering precise angle control for grading, sloping, and finish work, without sacrificing power or torque.

4. Lifting Eye

A reliable lifting eye, ensuring safe handling of loads even when the attachment is angled.

5. ISO Hook

A self-contained ISO-certified safety mechanism that prevents attachment loss when rotating or tilting, even in the event of hydraulic failure.

6. Cast Frame

A curved, high strength cast frame that remains lightweight to support tilt functionality while providing durability for challenging tasks.

BENEFITS

Increased Versatility

Access hard to reach areas with ease

Improved Productivity

Increase the yield on jobs, driving profitability

Low Maintenance

Designed with fewer parts, there is less to maintain

SPECIFICATION

GTT Range	Excavator Mass (t)	Coupler Mass (kg)	Pin Diameter (mm)	Rotation (°)	Min Pickup Width (mm)	Pin Pickup Range (mm)
Range 0A	1-1.5	32.9 - 34.2	30	180	94 / 96	85 - 118
Range 0B	1.5 - 2	34.9 - 35.5	30	180	103	121 - 161
Range 1A	2	87.7 - 89.0	35	180	105	125 - 150
Range 1B02	2 - 3	90.8 - 92.7	35	180	117	160 - 200
Range 1B01	3 - 3.5	94.4 - 95.5	38/40	180	117	172 - 215
Range 2A	5	125.9 -	45	180	144	220 - 285

Visit www.millergroundbreaking.com/products/coupler/gtt/ to configure your coupler needs.



GT Series

